

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
13 January 2005 (13.01.2005)

PCT

(10) International Publication Number
WO 2005/003803 A1

(51) International Patent Classification⁷: G01R 33/561

(21) International Application Number:
PCT/CH2004/000386

(22) International Filing Date: 24 June 2004 (24.06.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
03015094.0 3 July 2003 (03.07.2003) EP

(71) Applicants (for all designated States except US): UNI-
VERSITÄT ZÜRICH (CH/CH); Prorektorat Forschung,
Rämistrasse 71, CH-8006 Zürich (CH). ETH ZÜRICH
(CH/CH); BTH Transfer, Rämistrasse 101, CH-8092
Zürich (CH).

(72) Inventors; and

(75) Inventors/Applicants (for US only): PRUESSMANN,

Klaas [DE/CH]; Hopfenstrasse 15, CH-8045 Zürich (CH).
TSAO, Jeffrey [CA/CH]; Gempenstrasse 46, CH-4053
Basel (CH).


(74) Agent: SPIERENBURG & PARTNER AG; Mellinger-
strasse 12, CH-5443 Niederrohrdorf (CH).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, GR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MY, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

[Continued on next page]

(54) Title: MINIMUM NORM SENCE RECONSTRUCTION FOR OPTIMAL SPATIAL RESPONSE



(57) Abstract: A novel magnetic resonance imaging method is described, wherein undersampled magnetic resonance signals are acquired by a receiver antenna system having spatial sensitivity profiles and the image being reconstructed from the undersampled magnetic resonance signals and the spatial sensitivity profiles. The reconstruction of the image is provided by an optimization of a cost function which accounts for any of noise statistics, signal statistics, and the spatial response function, the latter of which is defined by the spatial signal response from the object to be imaged, separately for each individual pixel.

BEST AVAILABLE COPY

WO 2005/003803 A1